





Optional 2-Unit (19 Inch) Rack Mount

TECHNICAL SPECIFICATIONS

The F50/50/50-4LCM Quad Fiber Passive TAP provides permanent access into four multi-mode fiber links. This network TAP is ideal for security applications, network monitoring and anywhere you need to see all the data that only an In-Line solution can provide. Invisible to the network and non-powered, fiber TAPs will not affect network performance or integrity.

- Passive, non-powered design
- Four TAPs allow you to connect to one tool per link; tools require a dual NIC card to receive both sides of the conversation
- Supports multiple topologies, including Gigabit Ethernet, ATM, OC3-OC48 and SONET
- View layer 1 and 2 errors not seen when performing network monitoring using SPAN ports
- Available with custom split ratios upon request
- Space saving design allows you to TAP up to eight links in 1U

TAP Connections	
Four Links Tapped Dual LC	
Monitor Ports	
Four Tools Dual LC	
Split Ratio	
50/50	
Additional Split Ratios Available	
Insertion Loss	
4.0 dB Insertion Loss Max.	
Physical Dimensions (HxWxD)	
1.13 x 8.75 x 7.75 in (2.86 x 22.22 x 19.69 cm)	
Weight	
1.10 lbs (0.49 kgs)	
Environmental	
Operating Temperature: 32° to 104°F (0° to 40°C)	
Storage Temperature: -22° to 149°F (-30° to 65°C)	
Humidity: 5 to 90% non-condensing	
Warranty	
Two (2) Year Limited Warranty	
Order Information	
Product	Description
F50/50/50-4LCM	Quad Fiber Passive TAP
	OC3-OC48, 1000SX (50
	micron) 50/50 split ratio
	w/ LC Connectors
RMC-2	2 Tap 1U Rack Mount
KWIC-2	Chassis
	01100010

ACCESS YOUR NETWORK[™] Contact NextGig Systems 805-277-2400 NextGigSystems.com